






▼ SELECTION CHART





For use with Cylinder Capacity (tons)	Saddles			Base Plate	Mounting Block	Clevis Eyes	
	Flat	Grooved ¹⁾	Tilt			Base ⁴⁾	Plunger
							
5	A53F ²⁾	A53G ²⁾	—	—	RB5 ²⁾ , AW51 ²⁾ , AW53 ²⁾	REB5 ²⁾	REP5 ²⁾
10	A12 ⁵⁾ , A102F ³⁾	A102G ³⁾	CATS12 ³⁾	JB110 ³⁾	RB10, AW102	REB10	REP10 ³⁾
15	—	A152G	CATS12	—	RB15	REB15	REP10
25	A29 ⁵⁾	A252G	CATS52	JB125	RB25	REB25	REP25
30	A29 ⁵⁾	A252G	CATS52	—	RB25	—	REP25
50	—	—	CATS100	JB150	—	—	—
75	—	—	CATS100	—	—	—	—
100	—	—	CATS100	—	—	—	—



¹⁾ Standard on 5-30 tons RC-cylinders ²⁾ Except RC50 ³⁾ Except RC101 ⁴⁾ Mounting screws are included. ⁵⁾ Used with Bender Sets.

▼ DIMENSION CHARTS

Model Number	Saddle Dimensions (in)			A53F, A102F A12, A29	For Cylinder Capacity (tons)	Tilt Saddle Model Number	Addition to Collapsed Height A1 (in)	Saddle Diameter J1 (in)	
	A	B	C						
	Flat								
A53F	1.00	0.25	0.68		10	CATS12	0.55	1.38	
A102F	1.38	0.24	0.88		15	CATS12	0.43	1.38	
A12	2.00	1.88	1"-8 UNC		25	CATS52	0.59	1.97	
A29	2.00	1.88	1½"-16 UNC		30	CATS52	0.59	1.97	
	Grooved				50	CATS100	0.59	2.80	
A53G	1.00	0.25	0.68		75	CATS100	0.59	2.80	
A102G	1.38	0.24	0.88		100	CATS100	0.59	2.80	
A152G	1.50	0.37	0.88						
A252G	1.97	0.37	1.40						

Model Number	Base Plate Dimensions (in)					
	A	B	C	D	E	
JB110	9.00	9.00	5.34	2.29	0.81	
JB125	11.00	11.00	5.53	3.41	1.03	
JB150	12.00	0.60	3.75	5.19	1.25	

Model Number	Mounting Block Dimensions (in)								
	A	B	C	D	E	F	G	H	
RB5	1½"-16UN	3.50	3.00	—	1.00	—	—	—	
AW51	1½"-16UN	2.76	2.36	0.43	0.98	2.13	¼"-16 UN	1.62	
AW53	1½"-16UN	2.87	0.28	0.31	0.75	2.25	¼"-20 UN	0.41	
RB10	2¼"-14UN	4.50	3.50	—	1.00	—	—	—	
AW102	2¼"-14UN	3.94	3.25	0.63	1.18	3.00	7/16"-20 UN	2.31	
RB15	2¾"-16UN	4.00	4.50	—	1.50	—	—	—	
RB25	3¾"-12UN	5.00	6.50	—	2.00	—	—	—	

Type	Model Number	Clevis Eye Dimensions (in)						Pin-to-Pin * (in)	
		A	B	C	D	E	F		
Base ⁴⁾	REB5	1.75	1.88	0.56	0.63	0.63	1.00	2.37	
	REB10	2.50	2.63	1.00	0.88	1.00	1.38	3.07	
	REB15	3.00	2.63	1.00	0.88	1.00	1.38	3.07	
	REB25	3.75	3.13	1.50	1.25	1.25	1.63	3.45	
Plunger	REP5	1.13	1.75	0.56	0.63	0.63	0.75	—	
	REP10	1.69	2.43	1.00	0.88	1.00	1.13	—	
	REP25	2.25	2.81	1.50	1.25	1.25	1.38	—	

⁴⁾ Mounting screws are included.

* Pin to Pin – REB and REP Clevises fitted. Add cylinder collapsed height.