



Tipo : Type :	E5/LS600	do: 5 mm	36
------------------	----------	----------	----

Omologazione Homologation	PN	Coefficiente efflusso ridotto Low flow coefficient	Campo di taratura Setting range
CE - UKCA	700	0,828	301,0 - 600,0 bar
EAC	700	0,828	301,0 - 600,0 bar
ATEX Ex h II 2 Gb - UKEX	700	0,828	301,0 - 600,0 bar
ATEX Ex h II 2 Db - UKEX	700	0,828	301,0 - 600,0 bar
ASME XIII - CRN (Canada)	700	0,629	301,0 - 600,0 bar
SELO - TSG	700	0,629	301,0 - 420,0 bar

CONFIGURAZIONE - CONFIGURATION			
Materiale Material	Ottone Brass	Mista Ottone-Acciaio inox Mixed Brass-Stainless steel	Acciaio inox Stainless steel
Modelli Model	/	/	Senza Ghiera Without ring nut
	/	/	/
	/	/	/
	/	/	/
	/	/	/
	/	/	/
	/	/	/
Sedi di Tenuta Seal System	/	/	VESPEL -196 / + 250 °C
	/	/	/
	/	/	/
	/	/	/
	/	/	/
	/	/	/
	/	/	/
Connessione Entrata Inlet Connection	/	/	G.3/4" - 1" ISO228
	/	/	R.3/4" - 1" EN10226
	/	/	3/4" - 1" NPT
	/	/	/
	/	/	/
	/	/	/
	/	/	/
Connessione Uscita Outlet Connection	/	/	G.1" ISO228
	/	/	/
	/	/	/
	/	/	/
	/	/	/
	/	/	/
	/	/	/

A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPEL), TÜV, RINA, Bureau Veritas, ABS e Lloyd Register.
On request tests can be made by the most prestigious societies, such as: INAIL (area ISPEL), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.

Note: